



TT-399 Keramik fedt

PREMIUM ASSEMBLY PASTE AND LUBRICANT GREASE

- ✓ Reduces friction.
- ✓ Prevents electrolytic corrosion.
- ✓ Withstands high temperatures and high pressure.

Technical Info

- Aspect: pasta-like in aerosol.
- Colour: beige.
- Flash point: >101°C.
- Relative density at 20°C: 1 kg/L.

Packing

TT-399 Keramik fedt - cartridge 200ml

TT399

Product

Characteristics

TT- 399 has a very high temperature range (peak temperature approx. 1500 °C) and a high resistance to pressure. At the same time, it reduces the friction in the moving parts and provides effective protection against corrosion. As TT-399 is an assembly paste without metal particles, it also provides outstanding protection against electrolytic corrosion. This type of corrosion occurs when different metals come into contact with one another, such as a steel bolt screwed into an aluminum component. Without protection the least precious metal (in this instance, aluminum) will be affected.

Applications

Assembly/disassembly of: ABS and ASR system components, brake parts, spark plugs (glow plugs), lambda sensors, exhaust parts, (bolt) connections, connections of different metals (e.g. steel/aluminum), a range of connections and flanges in industry and furnaces.

Ideal for protection of components and applications exposed to very high temperatures and/or high pressures.

Use