

TT-518 Transfix



TRANSPARENT ADHESIVE WITH 700% ELASTICITY

- ✓ Adheres to porous and smooth surfaces, even to polypropylene (without primer).
- ✓ Permanently flexible and paintable.
- ✓ Can even be used under water.

Technical Info

- Colour: transparent.
- Smell: ether.
- Hardness: 75-85 Shore A.
- Tensile strength: 21 N/mm².
- Elongation: 700%.
- Dielectric resistance: 500 Volt/mm (25 Micron).
- Temperature resistance: -84°C till +100°C.
- Working time: 10 minutes.
- Curing at 20°C:
 - 8 hours - 70%
 - 24 hours - 100%
- Chemical resistance: excellent -nitric acid (20%) - acetates (10%) -sulphuric acid (10%) -lactic acid (5%) -hydrochloric acid (20%) -boric acid -alcohols -food -oils -seawater -phenols
- Shelf life: 5 years, in sealed package, keep dry, cool and frost-free.
- Safety measures: consult the Safety Data Sheet.

Packing

TT-518 Transfix - tube 95ml

505020118

Product

Characteristics

This monocomponent transparent paste adheres to most materials and is extremely flexible after curing. This makes Transfix extremely suitable for joining, sealing or repairing materials with a large difference in expansion coefficient.

Applications

- repair of tarpaulins, seat covers, flexible pipes in PVC, polypropylene, rubber or vinyl.
- repairing holes and cracks in plastic fabrics (rubber boats, buoys, rain gear).
- adheres to metal, wood, glass, leather, linen, canvas, vinyl and even polypropylene.

Use

- Clean and dry substrates - sand smooth surfaces.
 - Apply Transfix on both surfaces; join together after 5 minutes.
- Apply more Transfix to very porous substrates. Apply thick coats in different thin layers. Smooth seams with TT-1014 Sikker Afrens FS. Skin formation after 10 minutes - complete curing after 24 h.